



POR-15® Restoration Products

POR-15 Rubberized Under Coating

Application Information

PRODUCT DESCRIPTION:

POR-15 Rubberized Under Coating is a flexible, paintable, black coating. It's an excellent moisture barrier for application over auto underbody repairs and creates an effective sound barrier that reduces vibration and deadens sound in wheel wells, quarter panels, fenders, frames and undercarriages.

Directions for Use:

1. Remove all loose rust, dirt, grease and wax from surface to be coated using POR-15 Marine Clean, diluting solution 5 parts water to 1 part Marine Clean. Bare metal should be primed, using POR-15 for permanent rust protection.
2. Shake can well for at least 1 minute once mixing ball begins to move in can.
3. Spray from a distance of 12 -16 inches from surface applying in uniform coats.
4. Allow coating to dry for 1 hour before touching. May recoat anytime if necessary.
5. To prevent spray valve from clogging after use, turn can upside down and spray for about 3 seconds or until free of material.

CONTAINS: Liquefied Petroleum Gas (CAS #68476-86-8), Toluene (CAS #108-88-3), t-Butyl Acetate (CAS #540-88-5), PM Acetate (CAS #108-65-6), Acetone (CAS #67-64-1), and VM&P Naphtha (CAS #64742-89-8)

DANGER: CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE.

Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120F. Harmful or fatal if swallowed. Use only with adequate ventilation. Irritating to skin and eyes.

WARNING: This product contains chemicals know to the state of California to cause cancer, birth defects or other reproductive harm.

FIRST AID: In case of eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash with soap and water. If overcome by vapors, remove to fresh air. If swallowed, do not induce vomiting, contact physician immediately.

VOC CONTENT - ABP Maximum MIR 1.55

KEEP OUT OF THE REACH OF CHILDREN